

# statements | TILE & STONE

## Marvel Edge

Unglazed Color Body Porcelain Tile

Thickness: 9mm

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≤0.1%
Break Strength	C648	ISO-10545/4	S ≥ 1500 N R ≥ 40 N/mm <sup>2</sup>
Scratch Hardness	MOH's Scale	EN-101	5 (p), 6(m)
Chemical Resistance	C650	ISO-10545/13	UA ULA
Frost Resistance	C1026	ISO-10545/12	Resistant
Stain Resistance	C1378	ISO-10545/14	5
Deep Abrasion-Unglazed Tiles	C1243	ISO-10545/6	≤ 150 mm <sup>3</sup>
Dynamic Coefficient of Friction (DCOF)	A137.1	-	<0.42 Wet
Shade and Texture Rating	CTDA "V"	-	V2 (Elegant Sable, Gris) V3 (Absolute Brown)
Facial Dimensions	C499	ISO-10545/2	± 0.3% ± 1.0 mm
Range of Thickness	C499	ISO-10545/2	± 5.0% ± 0.5 mm
Warpage/Surface Flatness	C485	ISO-10545/2	± 0,3% ± 1,5 mm
Wedging/Rectangularity	C502	ISO-10545/2	± 0,3% ± 1,5 mm

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188